

GOOSENECK/FIFTH-WHEELS

ICON STACKER 8.5'W

SPECIFICATIONS	ICG/FS85 36TTA6	ICG/FS85 38TTA6	ICG/FS85 40TTA6	ICG/FS85 42TTA6	ICG/FS85 44TTA6	ICG/FS85 46TTA6	ICG/FS85 48TTA6
AXLES-TORSION	8000#	8000#	8000#	8000#	8000#	8000#	8000#
TIRE SIZE-RADIAL	17.5"	17.5"	17.5"	17.5"	17.5"	17.5"	17.5"
BRAKES	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC
TUBE FRAME	8" TUBE	8" TUBE	8" TUBE	8" TUBE	8" TUBE	8" TUBE	8" TUBE
HITCH BALL SIZE-GOOSENECK	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
CURB WEIGHT	12816#	13528#	14240#	14952#	15664#	16376#	17088#
HITCH WEIGHT	2563#	2706#	2848#	2990#	3133#	3275#	3418#
GVWR	24000#	24000#	24000#	24000#	24000#	24000#	24000#
PAYLOAD CAPACITY	11184#	10472#	9760#	9048#	8336#	7624#	6912#
OVERALL LENGTH	36'-6"	38'-6"	40'-6"	42'-6"	44'-6"	46'-6"	48'-6"
OVERALL WIDTH	8'-6"	8'-6"	8'-6"	8'-6"	8'-6"	8'-6"	8'-6"
OVERALL HEIGHT	13'4"	13'4"	13'4"	13'4"	13'4"	13'4"	13'4"
EXTERIOR BOX WIDTH	8'-4"	8'-4"	8'-4"	8'-4"	8'-4"	8'-4"	8'-4"
INTERIOR LOWER DECK LENGTH	28'	30'	32'	34'	36'	38'	40'
INTERIOR UPPER DECK LENGTH	8'-4"	8'-4"	8'-4"	8'-4"	8'-4"	8'-4"	8'-4"
INTERIOR WIDTH	8'-1"	8'-1"	8'-1"	8'-1"	8'-1"	8'-1"	8'-1"
WIDTH BETWEEN WHEEL WELLS	80-1/4"	80-1/4"	80-1/4"	80-1/4"	80-1/4"	80-1/4"	80-1/4"
INTERIOR HEIGHT	11'1"	11'1"	11'1"	11'1"	11'1"	11'1"	11'1"
INTERIOR RISER WALL HEIGHT	51"	51"	51"	51"	51"	51"	51"
INTERIOR ATTIC HEIGHT	82"	82"	82"	82"	82"	82"	82"
PLATFORM HGT/LOAD HGT	22"/18"	22"/18"	22"/18"	22"/18"	22"/18"	22"/18"	22"/18"
REAR DOOR	RAMP	RAMP	RAMP	RAMP	RAMP	RAMP	RAMP
REAR DOOR WIDTH	92"	92"	92"	92"	92"	92"	92"
REAR DOOR HEIGHT	96"	96"	96"	96"	96"	96"	96"
SIDE DOOR WIDTH	48"	48"	48"	48"	48"	48"	48"
SIDE DOOR HEIGHT	78"	78"	78"	78"	78"	78"	78"
CROSS MEMBERS O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.
WALL POSTS O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.
ROOF MEMBERS O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.