



# ALUMINUM



## ALUMINUM SILVER STAR TAG-A-LONG 5' & 6'W

SPECIFICATIONS	SSAC58SA	SSAC510SA	SSAC610SA	SSAC612SA
AXLES/SPRING	2990#	2990#	2990#	2990#
TIRES	15" RADIAL	15" RADIAL	15" RADIAL	15" RADIAL
BRAKES	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
TUBE FRAME	3"	3"	3"	3"
HITCH BALL SIZE	2"	2"	2"	2"
CURB WEIGHT	845#	996#	1005#	1105#
HITCH WEIGHT	95#	112#	136#	150#
GVWR	2990#	2990#	2990#	2990#
PAYLOAD CAPACITY	2145#	1994#	1985#	1885#
OVERALL LENGTH	12'-2"	14'-2"	14'-2"	16'-2"
OVERALL WIDTH	6'-8"	6'-8"	7'-8"	7'-8"
OVERALL HEIGHT	6'-8"	6'-8"	7'-8"	7'-8"
EXTERIOR BOX WIDTH	5'	5'	6'	6'
INTERIOR LENGTH	8'1"	10'1"	10'1"	12'1"
INTERIOR WIDTH	4'-9"	4'-9"	5'-9"	5'-9"
INTERIOR HEIGHT	60-1/4"	60-1/4"	72-1/4"	72-1/4"
PLATFORM HEIGHT	19"	19"	19"	19"
REAR DOOR	SINGLE	SINGLE	DOUBLE	DOUBLE
REAR DOOR WIDTH	4'-2"	4'-2"	5'-4"	5'-4"
REAR DOOR HEIGHT	4'-5"	4'-5"	5'-7"	5'-7"
SIDE DOOR WIDTH	N/A	N/A	32"	32"
SIDE DOOR HEIGHT	N/A	N/A	64"	64"
CROSS MEMBERS O.C.	24"O.C.	24"O.C.	24"O.C.	24"O.C.
WALL POSTS O.C.	24"O.C.	24"O.C.	24"O.C.	24"O.C.
ROOF MEMBERS O.C.	24"O.C.	24"O.C.	24"O.C.	24"O.C.

\* ADDING ELECTRIC BRAKES TO 5'W OR 6'W CHANGES GVWR TO 3500#