

## TAG-A-LONG

### STAR 6'W

SPECIFICATIONS	ST610SA	ST612SA	ST612TA2	ST614TA2
AXLES/SPRING	2990#	2990#	3500#	3500#
TIRES	15" RADIAL	15" RADIAL	15" RADIAL	15" RADIAL
BRAKES	OPTION	OPTION	ELECTRIC	ELECTRIC
TUBE FRAME	3" TUBE	3" TUBE	4" TUBE	4" TUBE
HITCH BALL SIZE	2"	2"	2-5/16"	2-5/16"
CURB WEIGHT	1145#	1300#	1720#	1895#
HITCH WEIGHT	155#	160#	258#	285#
GVWR	2990#	2990#	7000#	7000#
PAYLOAD CAPACITY	1845#	1690#	5280#	5105#
OVERALL LENGTH	14'-2"	16'-2"	16'-2"	18'-2"
OVERALL WIDTH	7'-8"	7'-8"	7'-8"	7'-8"
OVERALL HEIGHT	7'-8"	7'-8"	7'-9"	7'-9"
EXTERIOR BOX WIDTH	6'	6'	6'	6'
INTERIOR LENGTH	10'-2"	12'-2"	12'-2"	14'-2"
INTERIOR WIDTH	5'-8"	5'-8"	5'-8"	5'-8"
INTERIOR HEIGHT	6'-1"	6'-1"	6'-1"	6'-1"
PLATFORM HEIGHT	18"	18"	19"	19"
REAR DOORS	DOUBLE	DOUBLE	DOUBLE	DOUBLE
REAR DOOR WIDTH	5'-3"	5'-3"	5'-3"	5'-3"
REAR DOOR HEIGHT	5'-6"	5'-6"	5'-6"	5'-6"
SIDE DOOR WIDTH	32"	32"	32"	32"
SIDE DOOR HEIGHT	5'-4"	5'-4"	5'-4"	5'-4"
CROSS MEMBERS O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.
WALL POSTS O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.
ROOF MEMBERS O.C.	24"O.C.	24"O.C.	24"O.C.	24"O.C.

\*\*Adding electric brakes changes GVWR to 3500#\*\*