

GOOSENECK/FIFTH-WHEELS

STAR 8.5'W

SPECIFICATIONS	STG/F8536 TTA3	STG/F8540 TTA3	STG/F8544 TTA3	STG/F8536 TTA4	STG/F8540 TTA4	STG/F8544 TTA4	STG/F8548 TTA4
AXLES/SPRING	5200#	5200#	5200#	6000#	6000#	6000#	6000#
TIRE SIZE	15" RADIAL	15" RADIAL	15" RADIAL	16" RADIAL	16" RADIAL	16" RADIAL	16" RADIAL
BRAKES	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC
TUBE FRAME	6" TUBE	6" TUBE	6" TUBE	6" TUBE	6" TUBE	6" TUBE	8" TUBE
HITCH BALL SIZE-GOOSENECK	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
PIN BOX SIZE-FIFTH WHEEL	2"	2"	2"	2"	2"	2"	2"
CURB WEIGHT	6655#	7079#	7522#	6948#	7372#	7815#	8231#
HITCH WEIGHT	1664#	1770#	1881#	1737#	1843#	1954#	2058#
GVWR	15600#	15600#	15600#	18000#	18000#	18000#	18000#
PAYLOAD CAPACITY	8945#	8521#	8078#	11052#	10628#	10185#	9769#
OVERALL LENGTH	36'-6"	40'-6"	44'-6"	36'-6"	40'-6"	44'-6"	48'-6"
OVERALL WIDTH	8'-6"	8'-6"	8'-6"	8'-6"	8'-6"	8'-6"	8'-6"
OVERALL HEIGHT	9'	9'	9'	9'1"	9'1"	9'1"	9'3"
EXTERIOR BOX WIDTH	8'-4"	8'-4"	8'-4"	8'-4"	8'-4"	8'-4"	8'-4"
INTERIOR LOWER DECK LENGTH	28'	32'	36'	28'	32'	36'	40'
INTERIOR UPPER DECK LENGTH	8'-4"	8'-4"	8'-4"	8'-4"	8'-4"	8'-4"	8'-4"
INTERIOR WIDTH	8'-1"	8'-1"	8'-1"	8'-1"	8'-1"	8'-1"	8'-1"
WIDTH BETWEEN WHEEL WELLS	81-3/4"	81-3/4"	81-3/4"	81-1/2"	81-1/2"	81-1/2"	81-1/2"
INTERIOR HEIGHT	7'	7'	7'	7'	7'	7'	7'
INTERIOR RISER WALL HEIGHT	53"	53"	53"	53"	53"	53"	51"
INTERIOR ATTIC HEIGHT	31"	31"	31"	31"	31"	31"	31"
PLATFORM HGT	20"	20"	20"	21"	21"	21"	23"
REAR DOOR	DOUBLE	DOUBLE	DOUBLE	DOUBLE	DOUBLE	DOUBLE	DOUBLE
REAR DOOR WIDTH	7'-7"	7'-7"	7'-7"	7'-7"	7'-7"	7'-7"	7'-7"
REAR DOOR HEIGHT	6'-6"	6'-6"	6'-6"	6'-6"	6'-6"	6'-6"	6'-6"
SIDE DOOR WIDTH	48"	48"	48"	48"	48"	48"	48"
SIDE DOOR HEIGHT	6'-6"	6'-6"	6'-6"	6'-6"	6'-6"	6'-6"	6'-6"
CROSS MEMBERS O.C.	16" O.C.	16" O.C.	16" O.C.	16" O.C.	16" O.C.	16" O.C.	16" O.C.
WALL POSTS O.C.	16" O.C.	16" O.C.	16" O.C.	16" O.C.	16" O.C.	16" O.C.	16" O.C.
ROOF MEMBERS O.C.	24" O.C.	24" O.C.	24" O.C.	24" O.C.	24" O.C.	24" O.C.	24" O.C.