

## ALUMINUM STAR TAG-A-LONG 6' WIDE

SPECIFICATIONS	AST610SA	AST612SA	AST612TA2	AST614TA2
AXLES/SPRING	2990#	2990#	3500#	3500#
TIRES	15" RADIAL	15" RADIAL	15" RADIAL	15" RADIAL
BRAKES	OPTIONAL	OPTIONAL	ELECTRIC	ELECTRIC
TUBE FRAME	2" X 3"	2" X 3"	5" DOUBLE	5" DOUBLE
HITCH BALL SIZE	2"	2"	2-5/16"	2-5/16"
CURB WEIGHT	1035#	1141#	1498#	1651#
HITCH WEIGHT	140#	154#	197#	217#
GVWR	2990#	2990#	7000#	7000#
PAYLOAD CAPACITY	1955#	1849#	5502#	5349#
OVERALL LENGTH	14'-2"	16'-2"	16'-2"	18'-2"
OVERALL WIDTH	7'-8"	7'-8"	7'-8"	7'-8"
OVERALL HEIGHT	8'-1"	8'-1"	8'-3"	8'-3"
EXTERIOR BOX WIDTH	6'	6'	6'	6'
INTERIOR LENGTH	10'-2"	12'-2"	12'-2"	14'-2"
INTERIOR WIDTH	5'-9"	5'-9"	5'-9"	5'-9"
INTERIOR HEIGHT	77-3/4"	77-3/4"	77-3/4"	77-3/4"
PLATFORM HEIGHT	18"	18"	20"	20"
REAR DOORS	DOUBLE	DOUBLE	DOUBLE	DOUBLE
REAR DOOR WIDTH	5'-4"	5'-4"	5'-4"	5'-4"
REAR DOOR HEIGHT	6'-1"	6'-1"	6'-1"	6'-1"
SIDE DOOR WIDTH	32"	32"	32"	32"
SIDE DOOR HEIGHT	70"	70"	70"	70"
CROSS MEMBERS O.C.	16" O.C.	16" O.C.	16" O.C.	16" O.C.
WALL POSTS O.C.	16" O.C.	16" O.C.	16" O.C.	16" O.C.
ROOF MEMBERS O.C.	24" O.C.	24" O.C.	24" O.C.	24" O.C.