

## ALUMINUM SILVER STAR TAG-A-LONG 7.5'W

SPECIFICATIONS	SSAC7514TA2	SSAC7516TA2	SSAC7518TA2
AXLES/SPRING	3500#	3500#	3500#
TIRES	15" RADIAL	15" RADIAL	15" RADIAL
BRAKES	ELECTRIC	ELECTRIC	ELECTRIC
TUBE FRAME	5"	5"	5"
HITCH BALL SIZE	2-5/16"	2-5/16"	2-5/16"
CURB WEIGHT**	2244#	2475#	2706#
HITCH WEIGHT	292#	322#	352#
GVWR	7000#	7000#	7000#
PAYLOAD CAPACITY	4756#	4525#	4294#
OVERALL LENGTH	16'-1"	16'-1"	18'-1"
OVERALL WIDTH	8'-6"	8'-6"	8'-6"
OVERALL HEIGHT	8'-4"	8'-4"	8'-4"
EXTERIOR BOX WIDTH	7'-6"	7'-6"	7'-6"
INTERIOR LENGTH W/'V'	16'-7"	18'-7"	20'-7"
INTERIOR WIDTH	7'-3"	7'-3"	7'-3"
INTERIOR HEIGHT	78-3/4"	78-3/4"	78-3/4"
PLATFORM HEIGHT	20"	20"	20"
RAMP REAR DOOR***	MED DUTY	MED DUTY	MED DUTY
REAR DOOR WIDTH	7'	7'	7'
REAR DOOR HEIGHT	6'-2"	6'-2"	6'-2"
SIDE DOOR WIDTH	32"	32"	32"
SIDE DOOR HEIGHT	70"	70"	70"
CROSS MEMBERS O.C.	16"O.C.	16"O.C.	16"O.C.
WALL POSTS O.C.	16"O.C.	16"O.C.	16"O.C.
ROOF MEMBERS O.C.	24"O.C.	24"O.C.	24"O.C.

\*\*Curb weights are based on STD model with no options\*\*

\*\*\*Medium Duty Ramp Door w/Flap is the New Standard on 7'W Models.

Double Cargo Doors may be Optioned at No Charge.